AD-A048 902 NATIONAL BUREAU OF STANDARDS WASHINGTON D C F/G 20/3
DETERMINATION OF CHARGE OR POLARIZATION DISTRIBUTION ACROSS POL--ETC(U)
SEP 77 A S DEREGGI, C M GUTTMAN, F I MOPSIK N00014-78-F-0015
UNCLASSIFIED TR-6 NL

1 OF 1
AD A048902

END
DATE FILMED
2-78
DDC

AD No. ADA048902
DDC FILE COPY

(12)

OFFICE OF NAVAL RESEARCH

(15) Contract N00014-78-C-0015

Task No. NR 356-522

(9) Technical Report, #6

(14) TR-6

(6) Determination of Charge or Polarization Distribution Across Polymer Electrets by the Thermal Pulse Method and Fourier Analysis.

by

(10) A.S. DeReggi, C.M. Guttman, F.I. Mopsik
G.T. Davis, M.G. Broadhurst

Prepared for Publication in

Physical Review Letters

National Bureau of Standards
Bulk Properties Section
Washington, D.C. 20234

(11) Sept. 1977

(12) 13 p.

Reproduction in whole or in part is permitted for any purpose of the United States Government.

Approved for Public Release; Distribution Unlimited.

DDC
RECEIVED
JAN 23 1978
B

240800

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER: Technical Report #6	2. GOVT ACCESSION NO.
3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle): "Determination of Charge or Polarization Distribution Across Polymer Electrets by the Thermal Pulse Method and Fourier Analysis	5. TYPE OF REPORT & PERIOD COVERED: Technical Report #6
	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s): A.S. DeReggi, C.M. Guttman, F.I. Mopsik, G.T. Davis, and M.G. Broadhurst	8. CONTRACT OR GRANT NUMBER(s): N00014-78-0015 F new
9. PERFORMING ORGANIZATION NAME AND ADDRESS: National Bureau of Standards, Bulk Properties Section, Polymers Division, Washington, D.C. 20234	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS: NR-356-522
11. CONTROLLING OFFICE NAME AND ADDRESS: Office of Naval Research, Chemistry Program, Arlington, Va. 22217	12. REPORT DATE: September 1977
	13. NUMBER OF PAGES: 13
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report): Unclassified
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

According to attached distribution list.

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

To be published in Physical Review Letters

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Charge distribution; Fourier analysis; polarization distribution; polyvinylidene fluoride; pyroelectricity; thermal pulse; transient response; vinylidene fluoride copolymer

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

Fourier analysis, applied to the recently introduced thermal pulse method, yields new and unique relations between the time-dependent, pyroelectric response of a thin specimen and the Fourier coefficients of the charge or polarization distribution across its thickness. The new analysis is applied illustratively to thermal pulse data for a vinylidene fluoride copolymer electret.

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Ent...

DDC FILE COPY AD A063205

Determination of Charge or Polarization Distribution Across Polymer Electrets by the Thermal Pulse Method and Fourier Analysis

by

A.S. DeReggi, C.M. Guttman, F.I. Mopsik, G.T. Davis and M.G. Broadhurst
National Bureau of Standards
Washington, D.C. 20234

Abstract

Fourier analysis, applied to the recently introduced thermal pulse method, yields new and unique relations between the time-dependent, pyroelectric response of a thin specimen and the Fourier coefficients of the charge or polarization distribution across its thickness. The new analysis is applied illustratively to thermal pulse data for a vinylidenefluoride copolymer electret.

ACCESSION for
NTIS White Section ☑
DDC Buff Section ☐
UNANNOUNCED ☐
JUSTIFICATION _____
BY _____
DISTRIBUTION/AVAILABILITY CODES
Dist. AVAIL. and/or SPECIAL
A

Several new experimental methods have been proposed in recent Letters[1,2,3] to probe the spatial distribution of charge and/or polarization across the thickness of thin (thickness of order 10 μm) dielectric samples. These methods are currently of interest as means to study piezo- and pyroelectric polymers. The electron-beam method of Sessler et al.[1] has a resolution of ~1 μm, but is destructive in the sense that the measuring process irreversibly changes the quantities measured. Acoustical methods of generating a propagating pressure step[2] across a sample in order to measure its inhomogeneous piezoelectric response are non-destructive; but the step rise time requirements become severe if a resolution of 1 μm is desired (a resolution of 1 μm requires a step rise time of ≤ 0.5 ns assuming a sound velocity of 2000 m/s.) Thermal methods of producing transient inhomogeneous strain across a sample in order to measure its inhomogeneous pyroelectric response as, for example, in the Collins's thermal pulse method[3,4,5] are both non-destructive and comparatively easy to implement experimentally (thermal equilibration times are ~1 ms). However, because the thermal equilibration process is diffusive rather than propagative (wavelike), information contained in the experimental data about charge and/or polarization distributions is convoluted with a time-dependent temperature distribution and somehow must be deconvoluted. The major and often quoted[1,2,3,4,5] objection to the Collins thermal pulse method has been that the deconvolution procedure[3,4,5] yields <u>non-unique</u> charge and/or polarization distributions.

In this Letter, we show that the Collins' experiment yields the first few Fourier coefficients of the charge or polarization distribution, not the charge or polarization distribution itself as may be supposed from Collins' papers[1,2,3]. Further, we present expressions for the response which allow the Fourier coefficients to be determined from the experimental data by numerical or graphical analysis. We apply the new expressions to thermal pulse data for a copolymer of vinylidene fluoride with tetrafluoroethylene. This example illustrates both the power and the limitations of the thermal pulse method.

Consider, first, the temperature $T(x,t)$ at time t across a sample regarded as a slab of infinite extent and of thickness d (see inset in Fig. 1) after a radiant heat pulse of duration t_r has been applied to the surface $x=0$. Assume that 1) the aluminum electrodes have negligible optical transmission and negligible thermal mass; 2) heat flows in the x-direction only; and 3) the sample does not lose heat to the surroundings. The <u>initial</u> temperature $T(x,0)$ taken at the <u>end</u> of the thermal pulse is written

$$T(x,0) = T_1 + \Delta T\ (x,0) \tag{1}$$

where T_1 is the uniform temperature of the sample prior to the pulse, and $\Delta T(x,0)$ is the deviation from T_1. In practice, $\Delta T(x,0)$ is a sharply localized function extending from $x=0$ with a width $\xi \ll d$. The temperature at $t > 0$ is $T(x,t) = T_1 + \Delta T(x,t)$ where [6]

$$\Delta T(x,t) = a_o + \sum_{n=1}^{\infty} a_n \cos(n\pi x/d) \exp(-n^2 t/\tau_1), \tag{2}$$

where $\tau_1 = d^2/(\pi^2 k)$ where k is the thermal diffusivity, and where

$$a_o = \frac{1}{d} \int_o^d \Delta T(x,0)\, dx = \lim_{t \to \infty} \Delta T(x,t) \tag{3}$$

and

$$a_n = \frac{2}{d} \int_o^d \Delta T(x,0) \cos(n\pi x/d)\, dx, \text{ for } n=1,2,\ldots \tag{4}$$

In the limiting case where $\Delta T(x,0) \to \delta(x)$ all a_n's are

$$a_n = 2a_o, \text{ for } n=1,2,\ldots \tag{5}$$

However, for a general $\Delta T(x,0)$, the temperature at the surfaces are described by

$$\Delta T(0,t) = a_o + \sum_{n=1}^{\infty} a_n \exp(-n^2 t/\tau_1) \tag{6}$$

and

$$\Delta T(d,t) = a_o + \sum_{n=1}^{\infty} (-1)^n a_n \exp(-n^2 t/\tau_1). \tag{7}$$

Expressions (6) and (7) have been used previously as the basis for thermal diffusivity measurements[7]. In the present case, the dimensionless quantities $\Delta T(0,t)/a_o$ and $\Delta T(d,t)/a_o$ can be obtained by measuring the transient resistance of one or both electrodes as done by Collins[4]. Then the a_n/a_o's and τ_1 can be determined without knowing the detailed shape of the light pulse.

Consider, now, the inhomogeneous pyroelectric response. Assume that real charge of volume density $\rho(x)$ and elementary dipoles responsible for polarization $\vec{P}(x) = \hat{x}\, P(x)$ move reversibly when the sample thermally expands or contracts. Following Collins,[5] the open-circuit voltage due to charge, ΔV_ρ, and that due to polarization, ΔV_p, are

$$\Delta V_\rho(t) = \frac{\alpha_x - \alpha_\varepsilon}{\varepsilon\varepsilon_o} \int_o^d \rho(x) \int_o^x \Delta T(x',t)\, dx'\, dx, \tag{8}$$

and

$$\Delta V_p(t) = \frac{\alpha_p + \alpha_x - \alpha_\varepsilon}{\varepsilon\varepsilon_o} \int_o^d P(x)\, \Delta T(x,t)\, dx, \tag{9}$$

where α_x, α_ε, and α_p are temperature coefficients $(1/x)(dx/dT)$, $(1/\varepsilon)\,(d\varepsilon/dT)$, and $(1/P)\,(dP/dT)$ respectively, ε is the relative permittivity and ε_o is the permittivity of vacuum. Substitution of (2) into the above equations gives

$$\Delta V_\rho(t) = \frac{\alpha_x - \alpha_\varepsilon}{\varepsilon\varepsilon_o} \left[a_o A_o + \frac{d}{\pi} \sum_{n=1}^{\infty} \frac{a_n \cdot A_n}{n} \exp(-n^2 t/\tau_1)\right], \tag{10}$$

where

$$A_o = \int_o^d x\, \rho(x)\, dx \tag{11}$$

$$A_n = \int_o^d \rho(x)\, \sin(n\pi x/d)\, dx, \quad \text{for } n=1,2,\ldots \tag{12}$$

and

$$\Delta V_p(t) = \frac{\alpha_p + \alpha_x - \alpha_\varepsilon}{\varepsilon\varepsilon_o} [a_o B_o + \sum_{n=1}^{\infty} a_n \cdot B_n \exp(-n^2 t/\tau_1)], \tag{13}$$

where

$$B_o = \int_o^d P(x)\, dx \tag{14}$$

and

$$B_n = \int_o^d P(x) \cos(n\pi x/d)\, dx \quad \text{for } n=1,2,\ldots \tag{15}$$

It should now be noted that a_n, A_n and B_n are coefficients of Fourier series expansions for $\Delta T(x,0)$, $\rho(x)$ and $P(x)$ respectively if these are expanded as cosine, sine and cosine series respectively.

The foregoing analysis shows that the inhomogeneous pyroelectric response consists of exponentially decaying components with relaxation times τ_1/n^2. Measurement of this response yields Fourier coefficient combinations $(\frac{a_n}{a_o})$ $(\frac{A_n}{A_o})$ $(\frac{d}{\pi})$ in the charge case, or $(\frac{a_n}{a_o})$ $(\frac{B_n}{B_o})$ in the polarization case (or a linear combination of these in the mixed case). For sufficiently short pulse duration ($t_r \ll \tau_1/n^2$ up to the highest n of interest), the approximation $a_n/a_o \approx 2$ can be made. Otherwise, a_n/a_o can be obtained from a separate measurement of the transient resistance of the electrodes. Thus, Fourier coefficients of the charge or polarization distribution, A_n/A_o or B_n/B_o, can be determined up to terms with n of order $N = \sqrt{\tau_1/t_r}$. The spatial resolution of the thermal pulse experiment is roughly d/N.

Limiting cases of charge and polarization distributions are of interest. Note that if $\rho(x) \rightarrow \delta(x)$, then $\Delta V_\rho(t) \rightarrow 0$ (i.e., charge on surface $x = 0$ does not contribute to $\Delta V_\rho(t)$), while if $\rho(x) \rightarrow \delta(x-d)$, $\Delta V_\rho(t)$ becomes indistinguishable from $\Delta V_p(t)$ for uniform polarization. This is a manifestation of the electrostatic equivalence of $\rho(x)$ and $-dP/dx$. Note also that if $P(x) \rightarrow \delta(x)$, then $\Delta V_p(t)$ becomes proportional to $\Delta T(0,t)$ in (7), while if $P(x) \rightarrow \delta(x-d)$, then $\Delta V_p(t)$ becomes proportional to $\Delta T(d,t)$ in (8). This is a consequence of the symmetrical roles played by a_n and B_n.

Figure 1 shows signals proportional to open-circuit voltages for two copolymer samples 50 μm thick (vinylidenefluoride with 27% by weight of tetrafluoroethylene). For each sample Curve A is for light pulsed at x=0 and Curve B is for light pulsed at x=d. The difference in the samples is in the poling treatment. Both samples were stored for long periods under short-circuit conditions after poling. Sample (a) was poled at room temperature by corona charging[8] with a bias voltage of -2000 V. Curve A, shown in Figure 1(a) is nearly proportional to the $\Delta T(0,t)$ signal (not shown) at times $t >> t_r$ where $t_r \approx 20$ μs while Curve B is nearly proportional to $\Delta T(d,t)$. These observations indicate (assuming that all $B_n = 0$ for $n>N$) a sample with strong localization of polarization towards x=0 as shown qualitatively by (a) in the inset (or a sample with a charge layer imbedded just inside the sample close to x=0). Sample (b) was poled during crystallization by maintaining 300 V across the sample as it was cooled from 130°C and crystallized for 6 hours at 118.5°C before cooling further to 100°C (0.3 K/min) followed by quenching to room temperature. The signals for this case, shown in Figure 1(b), indicate a distributed asymmetric pyroelectric activity.

Note that series (10) and (13) acquire alternating signs if the direction of irradiation is changed (in which case a_n changes to $(-1)^n a_n$) or if the sample is reversed (in which case A_n and B_n change to $-(-1)^n A_n$ and $-(-1)^n B_n$). Thus, if separate response signals are obtained by thermally pulsing opposite surfaces in turn, the even and odd Fourier coefficients can be obtained separately from the sum and the difference of the two signals. Visual comparison of the two signals also reveals whether the distribution of pyroelectric responsivity is symmetric or asymmetric.

Figure 2 shows semi-log plots of the curves A and B from Figure 1(b) together with (A+B) containing only even terms of the response and (A-B) containing only odd terms of the response. Assume that the responses are associated with polarization. Graphical analysis of the linear part of the odd response gives $\tau_1 = 4.8$ ms (in good agreement with the value expected from the thermal properties and the thickness of the film) and $2a_1B_1 = 14$. Removal of this linear part gives a remainder (Curve D) with a slope $9/\tau_1$ indicating that $2a_3B_3 \simeq 1.5$ and that $2a_5B_5 \simeq 0$. Similar analysis of the even response gives $2a_oB_o = 10.2$, $2a_2B_2 \simeq 5$ (from Curve C) and $2a_4B_4 \simeq 0$. As the pulse duration of $t_r \simeq 20$ μs should allow about 10 terms to be observed ($N = \sqrt{\tau_1/t_r} > 10$), and terms for $n \geq 4$ do not appear in the pyroelectric response (though they appear in the x=0 resistance signal), it is concluded that the B_n's for $n \geq 4$ are negligible compared to the four leading coefficients. The values of a_2B_2 and a_3B_3 are then corrected to the values 2.675 and 0.775 respectively by forcing coefficients a_oB_o, $-a_1B_1$, a_2B_2, $-a_3B_3$ when inserted into (13) to yield a curve B' in Figure 2 within experimental uncertainty of measured Curve B. The polarization distribution obtained from the determined coefficients assuming $a_1 = a_2 = a_3 = 2a_o$ is the distribution (b) in the inset of Figure 1.

The samples discussed in this Letter were chosen to illustrate the theory. Other copolymer samples and homopolymer (polyvinylidenefluoride) samples under different poling conditions can exhibit nearly uniform polarization[9]. In such cases, the response is nearly step-like and $B_n/B_o = 0$ for all n.

The present work indicates the source of ambiguity in the Collins' deconvolution procedure. The thermal pulse data (under conditions similar to those in Collins' experiments) yields no more than 10 or 15 coefficients (based on $N = \sqrt{\tau_1/t_r}$). The Collins' electrical analog sought to obtain discrete distributions characterized by 20 adjustable parameters. Any discrete distribution (of which there are many) consistent with the determinable Fourier coefficients would reproduce the measured transients within the noise in the data.

Partial support of this work by the Office of Naval Research is gratefully acknowledged.

FIGURE CAPTIONS

FIGURE 1 — Inhomogeneous pyroelectric response of two copolymer samples: (a) sample with pyroelectric activity concentrated towards surface x=0; and (b) sample with distributed pyroelectric activity. Signals marked A are for thermal pulse applied to surface x=0 and those marked B for thermal pulse applied to surface x=d. Inset shows thermal pulse arrangment. Polymer samples have vacuum-deposited, reflecting (partially absorbing, non-transmitting) electrodes. Polarizations (a) and (b) shown in the inset are obtained from first few Fourier moments of corresponding signals.

FIGURE 2 — Graphical analysis of response of Fig. 1(b). A and B, experimental data; A + B and A - B are even and odd response (see text). The relaxation time $\tau_1 = 4.18$ ms, coefficients $a_oB_o = 5.1$, $a_1B_1 = 7$, $a_2B_2 = 2.675$, $a_3B_3 = 0.775$, $a_nB_n = 0$ for $n \geq 4$ are determined as explained in text. B' is a plot of Eq.(13) with a_n replaced by $(-1)^n a_n$ using these a_nB_n's. C and D represent the $n = 2$ and $n = 3$ terms respectively.


Al
Al
P(x)
$\Delta V_p(t)$
(a)
(b)
x
x=0
x=d
RESPONSE (ARBITRARY UNITS)
10
0
A
B
(a)
0
10
20
30
t, ms
10
0
A
B
(b)
0
10
20
30
t,ms

FIGURE 1


RESPONSE (ARBITRARY UNITS)
20
10
5
1
0.5
0
A+B
A
B
A-B
B'
C
D
0
5
10
TIME (ms)

FIGURE 2

References

1. G. M. Sessler, J. E. West, D. A. Berkley, and G. Morgenstern, Phys. Rev. Lett. 38, 368 (1977).
2. P. Laurenceau, G. Dreyfus, and J. Lewiner, Phys. Rev. Lett., 38, 4-6 (1977).
3. R. E. Collins, Appl. Phys. Lett., 26, 675 (1975).
4. R. E. Collins, Rev. Sci. Inst., 48, 83 (1977).
5. R. E. Collins, J. Appl. Phys., 47, 4804 (1976).
6. See for instance R. V. Churchill "Fourier Series and Boundary Value Problems", McGraw Hill 1941, p. 109.
7. W. J. Parker, R. J. Jenkins, C. P. Butler, and G. L. Abbott, J. Appl. Phys., 32, 1679 (1961).
8. A. D. Southgate, Appl. Phys. Lett., 28, 250 (1976).
9. M. G. Broadhurst, G. T. Davis, S. C. Roth, and R. E. Collins, Proceedings of the 45th Annual Conference on Electrical Insulation and Dielectric Phenomena, Buck Hill Falls, October 1976 (in press).

TECHNICAL REPORT DISTRIBUTION LIST

	No. Copies
Dr. Stephen H. Carr Department of Materials Science Northwestern University Evanston, Illinois 60201	1
Dr. M. Broadhurst Bulk Properties Section National Bureau of Standards U.S. Department of Commerce Washington, D.C. 20234	2
Dr. C. H. Wang Department of Chemistry University of Utah Salt Lake City, Utah 84112	1
Dr. T. A. Litovitz Department of Physics Catholic University of America Washington, D.C. 20017	1
Dr. R. V. Submaranian Washington State University Department of Materials Science Pullman, Washington 99103	1
Dr. M. Shen Department of Chemical Engineering University of California Berkeley, California 94720	1
Dr. R. S. Porter Polymer Research Institute and Polymer Science and Engineering University of Massachusetts Amherst, Massachusetts 01002	1
Dr. Morton Litt Dept. of Macromolecular Science Case Western Reserve University Cleveland, Ohio 44106	1
Dr. V. Stannett Department of Chemical Engineering North Carolina State University Raleigh, North Carolina 27607	1
Dr. D. R. Uhlman Department of Metallurgy and Material Science Center for Materials Science and Engineering Massachusetts Institute of Technology Cambridge, Massachusetts 02139	1
Naval Surface Weapons Center White Oak Silver Spring, Maryland 20910 Attn: Dr. J. M. Augl Dr. B. Hartmann	1
Dr. G. Goodman Globe Union Inc. 5757 North Green Bay Avenue Milwaukee, Wisconsin 53201	1
Picatinny Arsenal SMUPA-FR-M-D Dover, New Jersey 07801 Attn: A. M. Anzalone Bldg. 3401	1
Dr. J. K. Gillham Princeton University Department of Chemistry Princeton, New Jersey 08540	1
Douglas Aircraft Co. 3855 Lakewood Boulevard Long Beach, California 90846 Attn: Technical Library C1 290/36-84 AUTO-Sutton	1
Dr. E. Baer Department of Macromolecular Science Case Western Reserve University Cleveland, Ohio 44106	1
Dr. K. D. Pae Department of Mechanics and Materials Science Rutgers University New Brunswick, New Jersey 08903	1

TECHNICAL REPORT DISTRIBUTION LIST

	No. Copies
Office of Naval Research Arlington, Virginia 22217 Attn: Code 472	2
Office of Naval Research Arlington, Virginia 22217 Attn: Code 102IP	6
ONR Branch Office 536 S. Clark Street Chicago, Illinois 60605 Attn: Dr. George Sandoz	1
ONR Branch Office 715 Broadway New York, New York 10003 Attn: Scientific Dept.	1
ONR Branch Office 1030 East Green Street Pasadena, California 91106 Attn: Dr. R. J. Marcus	1
ONR Branch Office 760 Market Street, Rm. 447 San Francisco, California 94102 Attn: Dr. P. A. Miller	1
ONR Branch Office 495 Summer Street Boston, Massachusetts 02210 Attn: Dr. L. H. Peebles	1
Director, Naval Research Laboratory Washington, D.C. 20390 Attn: Library, Code 2029 (ONRL) Technical Info. Div. Code 6100, 6170	6 1 1
The Asst. Secretary of the Navy (R&D) Department of the Navy Room 4E736, Pentagon Washington, D.C. 20350	1
Commander, Naval Air Systems Command Department of the Navy Washington, D.C. 20360 Attn: Code 310C (H. Rosenwasser)	1
Defense Documentation Center Building 5, Cameron Station Alexandria, Virginia 22314	12
U.S. Army Research Office P.O. Box 12211 Research Triangle Park, North Carolina 27709 Attn: CRD-AA-IP	
Commander Naval Undersea Research & Development Center San Diego, California 92132 Attn: Technical Library, Code 133	1
Naval Weapons Center China Lake, California 93555 Attn: Head, Chemistry Division	1
Naval Civil Engineering Laboratory Port Hueneme, California 93041 Attn: Mr. W. S. Haynes	1
Professor O. Heinz Department of Physics & Chemistry Naval Postgraduate School Monterey, California 93940	
Dr. A. L. Slafkosky Scientific Advisor Commandant of the Marine Corps (Code RD-1) Washington, D.C. 20380	1

	No. Copies
NASA-Lewis Research Center 21000 Brookpark Road Cleveland, Ohio 44135 Attn: Dr. T. T. Serofini, MS-49-1	1
Dr. Charles H. Sherman, Code TD 121 Naval Underwater Systems Center New London, Connecticut	1
Dr. William Risen Department of Chemistry Brown University Providence, Rhode Island 02912	1
Dr. Alan Gent Department of Physics University of Akron Akron, Ohio 44304	1
Mr. Robert W. Jones Advanced Projects Manager Hughes Aircraft Company Mail Station D 132 Culver City, California 90230	1
Dr. C. Giori IIT Research Institute 10 West 35 Street Chicago, Illinois 60616	1
Dr. Jerome B. Lando Dept. of Macromolecular Science Case Western Reserve University Cleveland, Ohio 44106	1

	No. Copies
Dr. David Roylance Department of Materials Science and Engineerir Massachusetts Institute of Technology Cambridge, Massachusetts 02039	1
Dr. W. A. Spitzig United States Steel Corporation Research Laboratory Monroeville, Pennsylvania 15146	1
Dr. T. P. Conlon, Jr., Code 3622 Sandia Laboratories Sandia Corporation Albuquerque, New Mexico 87115	1
Dr. Martin Kaufmann, Head Materials Research Branch, Code 4542 Naval Weapons Center China Lake, California 93555	1
Dr. Charles Hicks Naval Undersea Center San Diego, California 92132	1
Mr. A. Johnson N43-12 National Highway Traffic Safety Admin. 2100 2nd Street, S.W. Washington, D.C. 20590	1